

15W Lily led scoop downlight range

Features In Brief:

1. Low heat, no UV or IR
2. Bridgelux COB technology
3. Aluminium alloy shell
4. Effective heat dissipation system
5. 20, 40, 60° beam angles
6. >50,000hrs (see website for details)



Heathfield LED scoop downlights are designed to replace the traditional ceramic metal halide downlights commonly seen within retail and used as display lighting. The solid construction of this unit offers uniformed light distribution. The downlight comes prewired with driver and has optional dimming capabilities for 1-10v/DALI/DSI. Using original CREE chips.

Part Number	Colour	Luminous Flux
HSCOOP15/5000K	5000K	1400 lm
HSCOOP15/4000K	4000K	1325 lm
HSCOOP15/3000K	3000K	1220 lm

*Based on 40° beam angle

15W Lily led scoop downlight Features

15w Range

Item	HSCOOP15/5000K	HSCOOP15/4000K	HSCOOP15/3000K
Input voltage	AC100-240V	AC100-240V	AC100-240V
Power consumption	15W	15W	15W
Beam angle	20, 40, 60°	20, 40, 60°	20, 40, 60°
Colour temperature	Daylight	Cool white	Warm white
Life time	>50,000 hrs	>50,000 hrs	>50,000 hrs
Operating temperature	-10°C to + 40°C	-10°C to + 40°C	-10°C to + 40°C
Storage temperature	-10°C to + 80°C	-10°C to + 80°C	-10°C to + 80°C
Lumen	1400lm	1325lm	1220lm
Certificates	CE . RoHS	CE . RoHS	CE . RoHS
Weight	300g	300g	300g
Cut Out	140mm cut out	140mm cut out	140mm cut out
CRI	80	80	80

Chromaticity Diagram

