

TRUE SOLAR OUTDOOR BOLLARD LIGHT 500mm IP65 ADJUSTABLE 40/220 /340LM 6W CCT ADJUSTABLE 3/4/6500K BLACK INTEGRAL

ILSBDB008



Designed for durability and performance, the Integral LED True Solar Round Top 500mm Bollard features a circular light with a downward-facing beam on top of a cylindrical post. With 3 CCT options to choose from there's a setting to suit any lighting scenario. Finished in black, this solar powered luminaire is built to withstand the harshest weather with an IP65 weatherproof rating. The built-in dusk till dawn PIR motion sensor ensures the light only comes on in the dark whilst the high-efficiency monocrystalline solar panel provides optimum energy conversion to the 2200mAh battery. Ideal for illuminating gardens, pathways and driveways, the True Solar Round Top Bollard combines modern style with long-lasting, energy-efficient lighting.

Details

Barcode:	5055788300786
Quick Order Code:	657396
Category:	Luminaires
Range Name:	Solar Lighting
Product Type:	Outdoor
Product Body Finish:	Black
Market Segment:	Residential Outdoor
Warranty (Years):	2
CE RoHS:	Yes

Physical Data

Product Length (mm):	500
Product Depth (mm):	200
Product Width (mm):	200
Product Weight (g):	900
Optic:	Opal Polycarbonate diffuser
Material:	Stainless steel body with powder coated, PC diffuser
Construction:	Monocrystalline solar panel, stainless steel body, PC diffuser
Luminaire Fixing:	Floor Mounted
Placement / Application:	Outdoor, General Lighting

Electrical Data

	6
Power Consumption (W) :	3.7
Input Voltage (V):	Non-Dimmable
Dimming:	DC
Electric Current:	EN-60598
EN:	Yes
LVD Certified:	

Light Data

Luminous Flux in Lumens (lm):	40/220/340
Correlated Colour Temperature (CCT) (K):	3000/4000/6500
Colour Temperature:	3000/4000/6500
Colour Temperature Name:	Warm White / Cool White / Cool Daylight
Beam Angle:	120
Colour Rendering Index (CRI):	80
LED Type:	Surface mounted device (SMD)
Lifetime (hours):	25000

Environment

EN:	EN-60598
LVD Certified:	Yes
CE RoHS:	Yes
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP65
Lowest Operating Temperature (°C):	-10
Maximum Operating Temperature (°C):	40

Packaging

Package Weight (g):	1280
Package Length (mm):	210
Package Width (mm):	210
Package Depth (mm):	525