

# TRUE SOLAR OUTDOOR SPIKE LIGHT 2 PACK IP44 60LM 0.5W 3000K BLACK INTEGRAL

ILSSKB013



Ideal for lighting pathways and garden borders, the True Solar Spike Light twin pack provides stylish illumination in any installation. Each spike light features a matt black finish, small cylindrical light with downward-facing beam and warm 3000K light, providing a modern look and welcoming atmosphere in any outdoor space. Powered by a high-efficiency monocrystalline solar panel with a 500mAh battery for long-lasting solar energy conversion.

## Details

<b>Barcode:</b>	5055788300830
<b>Quick Order Code:</b>	027585
<b>Category:</b>	Luminaires
<b>Range Name:</b>	Solar Lighting
<b>Product Type:</b>	Outdoor
<b>Product Body Finish:</b>	Black
<b>Market Segment:</b>	Residential Outdoor
<b>Warranty (Years):</b>	2
<b>CE RoHS:</b>	Yes

## Physical Data

<b>Product Length (mm):</b>	240
<b>Product Depth (mm):</b>	76
<b>Product Width (mm):</b>	76
<b>Product Weight (g):</b>	440
<b>Optic:</b>	Polycarbonate diffuser
<b>Material:</b>	Stainless steel body with powder coated, PC diffuser
<b>Construction:</b>	Monocrystalline solar panel, stainless steel body, PC diffuser
<b>Luminaire Fixing:</b>	Ground
<b>Placement / Application:</b>	Outdoor, General Lighting

## Electrical Data

<b>Power Consumption (W) :</b>	0.5
<b>Input Voltage (V):</b>	3.2
<b>Dimming:</b>	Non-Dimmable

<b>Electric Current:</b>	DC
<b>EN:</b>	EN-60598
<b>LVD Certified:</b>	Yes

## Light Data

<b>Luminous Flux in Lumens (lm):</b>	60
<b>Correlated Colour Temperature (CCT) (K):</b>	3000
<b>Colour Temperature:</b>	3000
<b>Colour Temperature Name:</b>	Warm White
<b>Beam Angle:</b>	120
<b>Colour Rendering Index (CRI):</b>	80
<b>LED Type:</b>	Surface mounted device (SMD)
<b>Lifetime (hours):</b>	25000

## Environment

<b>EN:</b>	EN-60598
<b>LVD Certified:</b>	Yes
<b>CE RoHS:</b>	Yes
<b>Hg 0% (Mercury Free):</b>	Yes
<b>IP Rating (Ingress Protection):</b>	IP44
<b>Lowest Operating Temperature (°C):</b>	-10
<b>Maximum Operating Temperature (°C):</b>	40

## Packaging

<b>Package Weight (g):</b>	500
<b>Package Length (mm):</b>	125
<b>Package Width (mm):</b>	60
<b>Package Depth (mm):</b>	250