



# Dura 30/40/50/60W Wattage Switchable LED CCT V2 Anti-Corrosive 6ft Batten

**Part Code: 10277V2** 

The Dura LED CCT Anti-Corrosive Batten is part of on of BELL's flagship luminaire families. This fitting takes the reliability of the Dura Batten and adds CCT & wattage switchable functionality.

- The ideal replacement for Single/Twin Fluorescent T5 and T8 fixtures
- Colour Switchable
- Wattage Switchable

















**Email:** technical@belllighting.co.uk **Telephone:** 01924 893380

www.belllighting.co.uk







Product Category	Fittings / Fittings
Application	LED Batten
<b>Product Warranty</b>	7 Years
EAN	5013588002828
Commodity Code	9405423100
Country of Origin	CN

Technical Specification		
Watts (W)	30/40/50/60	
Volts (V)	220/240	
Colour Temp (K)	3000/4000/6000	
Lumens (lm)	30W = 4438 (3000K) / 4842 (4000K & 6000K) - 40W = 5852 (3000K) / 6482 (4000K) / 6266 (6000K) - 50W = 7236 (3000K) / 8011 (4000K) / 7748 (6000K) - 60W = 8287 (3000K) / 9219 (4000K) / 8262 (6000K)	
Lumens per Watt (lm/W)	138-162	
CRI (ra)	85	
Frequency (Hz)	50/60	
LED Drive Current	90mA	
Energy Consumption (kWh/1000h)	60	
Life Hours	50000	
Switching Cycles	25000	
Impact Protection	IK10	
IP Rating	IP66	

Packaging Information		
Height (mm)	78	
Width (mm)	96	
Length (mm)	1870	
Diameter (mm)	20	
Individual Product Weight (kg)	2.2	
Single Carton Height (mm)	83	
Single Carton Width (mm)	100	
Single Carton Depth (mm)	1875	
Single Carton Weight (kg)	2.42	
Individual Volume	0.0155625	
Outer Box Qty	4	
Outer Carton Barcode	10277V2000004	
Outer Box Height (mm)	180	
Outer Box Width (mm)	215	
Outer Box Depth (mm)	1890	
Outer Box Weight (kg)	11.3	
Outer Box Volume	0.073143	

**Email:** technical@belllighting.co.uk **Telephone:** 01924 893380





Construction			
Primary Material	Polycarbonate		
	Electrical Information		

**Email:** technical@belllighting.co.uk **Telephone:** 01924 893380





120°
Samsung

**Email:** technical@belllighting.co.uk **Telephone:** 01924 893380