

# OUTDOOR IN GROUND UPLIGHT WITH H2O STOP IP67 115LM 4.5W 3000K PATHLIGHT 4 WAY BRUSHED ALUMINIUM INTEGRAL

ILGDA005



This stylish and practical recessed pathlight provides a four-way beam of light for highlighting paths and driveways, perfect for homes or hospitality venues. Hard-wearing and weatherproof, the die-cast aluminium body and aluminium dome bezel makes it suitable for coastal areas, and H2O STOP technology provides additional protection against moisture ingress through the electrical cables.

#### **Details**

**Barcode**: 5055788242222

Quick Order Code:478137Category:LuminairesRange Name:IngroundProduct Type:Outdoor

Product Body Finish: Brushed aluminium

Market Segment: Commercial and Residential outdoor

Warranty (Years): 3
CE RoHS: Yes

#### **Physical Data**

Product Depth (mm): 105
Product Weight (g): 500

Optic: Facetted Aluminium

Material: Die cast Aluminium with Aluminium Dome Bezel

Cut Out Diameter (mm): 82

Luminaire Fixing: Recessed

Placement / Application: Outdoor, General Lighting

#### **Electrical Data**

Power Consumption (W): 4.5

Voltage Range (v): 220-240

Dimming: Non-Dimmable

Driver Included: Yes
Electric Current: AC

**EN:** EN-60598

LVD Certified: Yes

### **Light Data**

Luminous Flux in Lumens (Im): 115 Correlated Colour Temperature (CCT) (K): 3000

Colour Temperature Name: Warm White

Colour Rendering Index (CRI):80Frequency Range (Hz):50/60Instant on (Less than 1 second):Yes


**LED Type:** Chip-on-board (COB)


Lifetime (hours): 25000 Switching Cycles: 12500

#### **Environment**

**EN:** EN-60598

LVD Certified: Yes **CE RoHS:** Yes **New Energy Rating:** G **EU Luminaire:** L Hg 0% (Mercury Free): Yes **IP Rating (Ingress Protection): IP67 Lowest Operating Temperature (°C):** -20 **Maximum Operating Temperature (°C):** 50





## **Packaging**

Package Weight (g): 530
Package Length (mm): 95
Package Width (mm): 95
Package Depth (mm): 170