

**GLS BULB WITH DUSK TO DAWN DUAL SENSOR E27 806LM 8W 2700K  
NON-DIMM 240 BEAM FROSTED INTEGRAL**

ILGLSE27SC043



This 8W retro-fit Integral LED Auto Sensor Classic Globe (GLS) (large screw base) delivers a warm light equivalent to 60W. Because security lighting is on an average of 12 hrs. per day you can save over 30 GBP/44 EUR per bulb, per year on energy. It automatically switches ON at dusk and OFF at dawn, with dual 360 sensors to detect daylight from all angles. Ideal for external porches, walkways, paths and patios. To be used in suitable enclosed outdoor fittings.

**Details**

<b>Barcode:</b>	5055788218265
<b>Quick Order Code:</b>	695886
<b>Category:</b>	Lamps
<b>Range Name:</b>	Auto Sensor
<b>Product Type:</b>	GLS
<b>Market Segment:</b>	Commercial outdoor (with appropriate outdoor fitting), Residential outdoor (with appropriate outdoor fitting)
<b>Features:</b>	Dusk-to-Dawn
<b>Warranty (Years):</b>	3
<b>CE RoHS:</b>	Yes

**Physical Data**

<b>Product Length (mm):</b>	115
<b>Product Width (mm):</b>	60
<b>Product Weight (g):</b>	72
<b>Material:</b>	Aluminium, Polycarbonate
<b>Base Term:</b>	Edison screw
<b>Bulb Base:</b>	E27
<b>Construction:</b>	Plastic and Aluminium heat sink, polycarbonate diffuser
<b>Globe Finish:</b>	Frosted
<b>Globe Type:</b>	Classic Globe (GLS)
<b>Bulb Fixing:</b>	Pendant, Wall
<b>Bulb or Luminaire Shape:</b>	Round
<b>Placement / Application:</b>	Outdoor (with appropriate outdoor fitting), General Lighting

**Electrical Data**



<b>Power (W):</b>	8
<b>Power Consumption (W) :</b>	8
<b>Power Factor:</b>	0.5
<b>Voltage Range (v):</b>	220-240
<b>Wattage equivalent (W):</b>	60
<b>Amperage (mA):</b>	55
<b>Dimming:</b>	Non-Dimmable
<b>Driver IC Manufacturer:</b>	Silergy
<b>Driver Included:</b>	Yes
<b>Electric Current:</b>	AC
<b>EN:</b>	EN-62560
<b>LVD Certified:</b>	Yes

## Light Data

<b>Luminous Flux in Lumens (lm):</b>	806
<b>Luminous efficacy (lm/W):</b>	101
<b>Correlated Colour Temperature (CCT) (K):</b>	2700
<b>Colour Temperature Name:</b>	Warm
<b>Beam Angle:</b>	240
<b>Colour Rendering Index (CRI):</b>	80
<b>Frequency Range (Hz):</b>	50
<b>Instant on (Less than 1 second):</b>	Yes
<b>LED Type:</b>	Surface mounted device (SMD)
<b>Lifetime (hours):</b>	25000
<b>Switching Cycles:</b>	50000

## Environment

<b>EN:</b>	EN-62560
<b>LVD Certified:</b>	Yes
<b>CE RoHS:</b>	Yes
<b>Previous Energy Rating:</b>	A+
<b>New Energy Rating:</b>	F
<b>Hg 0% (Mercury Free):</b>	Yes
<b>IP Rating (Ingress Protection):</b>	IP20
<b>Lowest Operating Temperature (°C):</b>	-20
<b>Maximum Operating Temperature (°C):</b>	40



## Packaging

Package Weight (g):	60
Package Length (mm):	65
Package Width (mm):	65
Package Depth (mm):	130
Qty per euro pallet:	1200

[Portal.integral-led.com](https://portal.integral-led.com)