# CANDLE BULB E14 470LM 4.9W 4000K DIMMABLE 240 BEAM CLEAR INTEGRAL



ILCANDE14DE095

THIS ITEM IS NOW UPGRADED OR DISCONTINUED. CONTACT US TO FIND A REPLACEMENT PRODUCT.

This 4.9W retro-fit Integral LED Candle (clear finish, small screw, white base) delivers a dimmable, warm light and brightness, similar to a 40W filament bulb. It features high output LEDs and an anti-glare refractor. Ideal for living rooms, dining rooms, bedrooms and hotels, in classic or modern wall or floor/table lamp fittings and chandeliers.

### **Details**

Barcode:	5055788272595
Quick Order Code:	741329
Category:	Lamps
Range Name:	Everyday
Product Type:	Candle
Market Segment:	Commercial indoor, Residential indoor
Warranty (Years):	2
CE RoHS:	Yes
Physical Data	
Product Length (mm):	102
Product Width (mm):	35
Product Weight (g):	33
Material:	Aluminium, Plastic
Base Term:	Edison screw
Bulb Base:	E14
Construction:	Aluminium and Plastic heat-sink, Injection moulded
	diffuser
Globe Finish:	Clear
Globe Type:	Candle
Bulb or Luminaire Shape:	Oval
Placement / Application:	Indoor, General Lighting

4.9 4.9

## **Electrical Data**

Power (W):	
Power Consumption (W) :	

**Power Factor:** 0.4 Voltage Range (v): 220-240 Wattage equivalent (W): 40 Amperage (mA): 55 **Dimming:** Dimmable with compatible dimmers **Driver Included:** Yes **Electric Current:** AC EN: EN-62560 **LVD Certified:** Yes


### **Light Data**

Luminous Flux in Lumens (Im):	470
Luminous efficacy (Im/W):	96
Correlated Colour Temperature (CCT) (K):	4000
Colour Temperature:	4000K - Cool White
Colour Temperature Name:	Cool White
Beam Angle:	240
Colour Rendering Index (CRI):	80
Compatible Dimmers:	Varilight
Frequency Range (Hz):	50/60
Instant on (Less than 1 second):	Yes
LED Type:	Surface mounted device (SMD)
Lifetime (hours):	15000
Switching Cycles:	50000

#### **Environment**


EN:	EN-62560
LVD Certified:	Yes
CE RoHS:	Yes
Previous Energy Rating:	A+
New Energy Rating:	F
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	40

# Portal.integral-led.com



# Packaging

Package Weight (g):	60
Package Length (mm):	110
Package Width (mm):	50
Package Depth (mm):	50
Qty per euro pallet:	2880



## Portal.integral-led.com