

HI-BRITE DOWNLIGHT 45MM CUTOUT 9W 550LM 63LM/W 4000K 30 BEAM DIMMABLE FINISH-A BLACK INTEGRAL

ILDL45K008



Lux Hi-Brite range is uniquely designed to provide maximum lumen output from a very compact body. Minimum glare is achieved from a deep-recessed construction, guaranteeing comfortable light. Lux Hi-Brite downlights are ideal for applications requiring high performance in limited spaces, such as hospitality, retail or commerce. The stylish fixed and tiltable finishes can illuminate a wide range of areas. Complement with Lux Mini range for coherent multilevel lighting design.

Yes

Details

Barcode: 5055788250616

Quick Order Code: 117966 Category: **Downlights** Range Name: Lux Hi-Brite 45 **LED Downlights Product Type: Product Body Finish:** Matt Black **Market Segment:** Accent lighting Finish: Matt Black Fixed/Tiltable: Fixed Warranty (Years):

CE RoHS:

Physical Data

Product Depth (mm): 56
Product Weight (g): 200

Optic: PMMA lens Material: Aluminium

Overall diameter (mm): 60
Cut Out Diameter (mm): 45

Luminaire Fixing:Wall/Ceiling mountedPlacement / Application:Indoor, General Lighting

Electrical Data

Power (W): 9
Power Consumption (W): 9

Voltage Range (v): 220-240VAC 50/60Hz

Dimming:Dimmable

Priver Included:
Yes

EN: EN 60598, EN 55015, EN 61547, EN 61000

LVD Certified: Yes

Light Data

Luminous Flux in Lumens (Im): 550
Luminous efficacy (Im/W): 63
Correlated Colour Temperature (CCT) (K): 4000

Colour Temperature: 4000K - Cool White

Colour Temperature Name: Cool White

Beam Angle: 30
Colour Rendering Index (CRI): 80


LED Type: Chip-on-board (COB)


Lifetime (hours): 60000 Switching Cycles: 15000

Environment

EN: EN 60598, EN 55015, EN 61547, EN 61000

LVD Certified: Yes Yes **CE RoHS: New Energy Rating:** G **EU Luminaire:** L Hg 0% (Mercury Free): Yes **IP Rating (Ingress Protection):** IP20 **Lowest Operating Temperature (°C):** -10 **Maximum Operating Temperature (°C):** 40





Packaging

Package Weight (g): 270
Package Length (mm): 125
Package Width (mm): 110

Package Depth (mm): Portal.integral-led.com