

**ULTRA SLIM TILTABLE DOWNLIGHT 65MM CUTOUT 6.5W 650LM 100LM/W  
3000K 36 BEAM DIMMABLE WHITE INTEGRAL**

ILDL65L001



The Lux Ultra Slim high-end tiltable and dimmable downlight range impresses by offering stylish high-quality finish, ultra-low profile height of only 27mm, a modern look topped with a very efficient performance. A tiltable angle of up to 25 Degrees is ideal for directing light on to features or placement into a sloped ceiling. In addition to light output efficacy reaching up to 103lm/W, this ultra-slim downlight is available in cool white and warm white CCTs as well as a choice for four finishes for a contemporary look. The included tool-free, user-friendly loop-in/loop-out driver enables quick and easy installation. Achieve modern lighting designs by complementing the Lux Ultra Slim range with Integral Lux Fire downlights.

**Details**

<b>Barcode:</b>	5055788250036
<b>Quick Order Code:</b>	947567
<b>Category:</b>	Downlights
<b>Range Name:</b>	Lux Ultra Slim
<b>Product Type:</b>	LED Downlights
<b>Product Body Finish:</b>	Matt white
<b>Market Segment:</b>	Accent lighting
<b>Finish:</b>	Matt White
<b>Fixed/Tilttable:</b>	Tilttable
<b>Warranty (Years):</b>	3
<b>CE RoHS:</b>	Yes

**Physical Data**

<b>Product Depth (mm):</b>	27
<b>Product Weight (g):</b>	180
<b>Optic:</b>	PMMA diffuser
<b>Material:</b>	Aluminium
<b>Overall diameter (mm):</b>	83
<b>Cut Out Diameter (mm):</b>	65
<b>Luminaire Fixing:</b>	Recess mounted
<b>Placement / Application:</b>	Indoor, General Lighting

**Electrical Data**

<b>Power (W):</b>	6.5
-------------------	-----



<b>Power Consumption (W) :</b>	6.5
<b>Voltage Range (v):</b>	220-240VAC 50/60Hz
<b>Dimming:</b>	Dimmable
<b>Driver Included:</b>	Yes
<b>EN:</b>	EN 60598, EN 55015, EN 61547, EN 61000
<b>LVD Certified:</b>	Yes

## Light Data

<b>Luminous Flux in Lumens (lm):</b>	650
<b>Luminous efficacy (lm/W):</b>	100
<b>Correlated Colour Temperature (CCT) (K):</b>	3000
<b>Colour Temperature:</b>	3000K - Warm White
<b>Colour Temperature Name:</b>	Warm White
<b>Beam Angle:</b>	36
<b>Colour Rendering Index (CRI):</b>	80
<b>Instant on (Less than 1 second):</b>	Yes
<b>LED Type:</b>	Chip on board (COB)
<b>Lifetime (hours):</b>	50000
<b>Switching Cycles:</b>	100000

## Environment

<b>EN:</b>	EN 60598, EN 55015, EN 61547, EN 61000
<b>LVD Certified:</b>	Yes
<b>CE RoHS:</b>	Yes
<b>New Energy Rating:</b>	F
<b>EU Luminaire:</b>	L
<b>Hg 0% (Mercury Free):</b>	Yes
<b>IP Rating (Ingress Protection):</b>	IP40
<b>Lowest Operating Temperature (°C):</b>	-20
<b>Maximum Operating Temperature (°C):</b>	45



## Packaging

<b>Package Weight (g):</b>	210
<b>Package Length (mm):</b>	125

[Portal.integral-led.com](http://Portal.integral-led.com)

Product Design And Specification Subject To Change Or Modification Without Notice. Image For Illustration Only. E&OE

Package Width (mm):	110
Package Depth (mm):	50