

**TRUE SOLAR OUTDOOR WEDGE WALL LIGHT PIR IP65 220LM 1.5W 4000K  
BLACK INTEGRAL**

ILSWL001



The Integral LED True Solar Wedge Wall Light features a wedge-shaped design with a primary down-facing LED panel for general illumination and a secondary backlight providing a wall-wash effect. Utilising a monocrystalline solar panel, it efficiently charges a replaceable 1200mAh battery offering hours of night-time lighting. With an in-built dusk-to-dawn PIR motion sensor and three intelligent modes, this luminaire maximises energy savings. Perfect for a range of outdoor applications, including security, garden, and entrance lighting, it offers both performance and reliability for commercial and residential use, and is backed by a 2-year warranty.

**Details**

<b>Barcode:</b>	5055788299691
<b>Quick Order Code:</b>	431491
<b>Category:</b>	Luminaires
<b>Range Name:</b>	True Solar
<b>Product Type:</b>	Outdoor
<b>Product Body Finish:</b>	Black
<b>Market Segment:</b>	Residential Outdoor
<b>Warranty (Years):</b>	2
<b>CE RoHS:</b>	Yes

**Physical Data**

<b>Product Length (mm):</b>	144
<b>Product Depth (mm):</b>	79
<b>Product Width (mm):</b>	96
<b>Product Weight (g):</b>	210
<b>Optic:</b>	Polycarbonate diffuser
<b>Material:</b>	Anti-UV ABS body
<b>Luminaire Fixing:</b>	Wall Mounted
<b>Placement / Application:</b>	Outdoor, General Lighting

**Electrical Data**

<b>Power Consumption (W) :</b>	1.5
<b>Dimming:</b>	Non-Dimmable
<b>Driver Included:</b>	Yes

<b>Electric Current:</b>	DC
<b>EN:</b>	EN-60598
<b>LVD Certified:</b>	Yes

## Light Data

<b>Luminous Flux in Lumens (lm):</b>	220
<b>Correlated Colour Temperature (CCT) (K):</b>	4000K front and 3000K back
<b>Colour Temperature:</b>	4000K front and 3000K back
<b>Colour Temperature Name:</b>	Cool White
<b>Beam Angle:</b>	90
<b>Colour Rendering Index (CRI):</b>	80
<b>LED Manufacturer:</b>	EVERLIGHT
<b>Lifetime (hours):</b>	35000

## Environment

<b>EN:</b>	EN-60598
<b>LVD Certified:</b>	Yes
<b>CE RoHS:</b>	Yes
<b>Hg 0% (Mercury Free):</b>	Yes
<b>IP Rating (Ingress Protection):</b>	IP65
<b>Lowest Operating Temperature (°C):</b>	-20
<b>Maximum Operating Temperature (°C):</b>	50

## Packaging

<b>Package Weight (g):</b>	270
<b>Package Length (mm):</b>	121
<b>Package Width (mm):</b>	106
<b>Package Depth (mm):</b>	105