

**TRUE SOLAR OUTDOOR WALL LIGHT IP65 ADJUSTABLE 40/220/340LM 6W
CCT ADJUSTABLE 3/4/6500K BLACK INTEGRAL**

ILSWLB007



Designed for durability and performance, the Integral LED True Solar Round Top Wall Light features a circular light with a downward-facing beam on top of a wall-mounted cylindrical arm. With 3 CCT options to choose from there's a setting to suit any lighting scenario. Finished in black, this solar powered luminaire is built to withstand the harshest weather with an IP65 weatherproof rating. The built-in dusk till dawn PIR motion sensor ensures the light only comes on in the dark whilst the high-efficiency monocrystalline solar panel provides optimum energy conversion to the 2200mAh battery. Ideal for illuminating gardens, patios, and doorways, the True Solar Round Top Wall Light combines modern style with long-lasting, energy-efficient lighting.

Details

Barcode:	5055788300779
Quick Order Code:	996775
Category:	Luminaires
Range Name:	Solar Lighting
Product Type:	Outdoor
Product Body Finish:	Black
Market Segment:	Residential Outdoor
Warranty (Years):	2
CE RoHS:	Yes

Physical Data

Product Length (mm):	220
Product Depth (mm):	182
Product Width (mm):	200
Product Weight (g):	700
Optic:	Opal Polycarbonate diffuser
Material:	Stainless steel body with powder coated, PC diffuser
Construction:	Monocrystalline solar panel, stainless steel body, PC diffuser
Luminaire Fixing:	Wall Mounted
Placement / Application:	Outdoor, General Lighting

Electrical Data

	6
Power Consumption (W) :	3.7
Input Voltage (V):	Non-Dimmable
Dimming:	DC
Electric Current:	EN-60598
EN:	Yes
LVD Certified:	

Light Data

Luminous Flux in Lumens (lm):	40/220/340
Correlated Colour Temperature (CCT) (K):	3000/4000/6500
Colour Temperature:	3000/4000/6500
Colour Temperature Name:	Warm White / Cool White / Cool Daylight
Beam Angle:	120
Colour Rendering Index (CRI):	80
LED Type:	Surface mounted device (SMD)
Lifetime (hours):	25000

Environment

EN:	EN-60598
LVD Certified:	Yes
CE RoHS:	Yes
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP65
Lowest Operating Temperature (°C):	-10
Maximum Operating Temperature (°C):	40

Packaging

Package Weight (g):	950
Package Length (mm):	220
Package Width (mm):	210
Package Depth (mm):	200