

## DELUX UNVENTED



The DeXpro Delux Digital unvented water heaters are ideal for use in light commercial applications such as, offices, shops, factories, schools/universities, hospitals, modular buildings or domestic applications often when there is no gas supply.

The DeXpro Delux Digital unvented will deliver mains pressure hot water to 1 or multiple outlets. See our size guide for assistance on selecting the correct size for your needs.

**Built to last, quality assured** The steel tank and connection pipes have a blue diamond enamel coating that is rust proof and corrosion resistant.

**Economically friendly** The tank has extremely dense CFC-FREE insulation that if the power is turned off to the appliance the water temperature will be maintained up to 48hrs.

- 6, 10 & 15 Litre storage capacity
- Digital temperature display
- 2.0kW Element for rapid heat up
- High Grade SS316 Stainless Steel Heating Element
- Blue diamond enamel coating on inner steel tank and inlet/outlet
- High density insulation CFC-FREE polyurethane
- Anti-corrosion and energy saving protection
- External temperature control
- Magnesium anode protection
- Empty heat up and overheat protection
- Manually re-settable thermal cut-out
- Floor standing or wall mounted
- Mains pressure (unvented) unit max. working pressure 6 bar
- Max. working temperature 75°C
- Brass safety pressure relief valve supplied

## KEY FEATURES



3 CAPACITY  
OPTIONS



2.0KW RAPID  
HEAT UP



TEMPERATURE  
CONTROL



CERTIFIED APPROVED

ERP Energy rating:

B

The accessory kit DXUKIT1 may be required depending on where the appliance is installed. The supplied 6 bar pressure relief valve must be installed and plumbed to the nearest external drain. Refer to the unvented diagrams on page 10.



Additional Expansion Vessel  
DXUKIT1

## SIZE GUIDE

## DXU6D

6 Litre | 1-2 Basins



## DXU10D

10 Litre | 2-3 Basins



## DXU15D

15 Litre | 3-4 Basins



Usage requirements vary depending on application. Contact our team for advice.

## DIMENSIONS

## FRONT

280MM (6L)  
360MM (10L)  
370MM (15L)



280MM (6L)  
350MM (10L)  
360MM (15L)

## SIDE



290MM (6L)  
300MM (10L)  
320MM (15L)

