

Heathfield 12W led PLL 2G11 lamp range

Features In Brief:

- 1. Energy saving exceeding 50%
- 2. Uniformed light distribution
- 3. Original epistar chips
- 4. Instant star, no flicking, no humming
- 5. Unique driver design
- 6. >50,000hrs (see website for details)



Heathfield LED lamps are designed to replace the traditional fluorescent type offering an energy saving alternative. The lamp is constructed of a high grade aluminium heat sync and custom designed light guide lens offering a uniformed light distribution, using our specifically designed driver and original epistar chips we can offer a stable operation with long life time claims and low optical decay levels.

Part Number	Colour	Luminous Flux
HPLL12/6000K	6000K	1200 lm
HPLL12/4000K	4000K	1140 lm
HPLL12/3000K	3000K	1080 lm




Heathfield 12W led PLL 2G11 lamp Features


12w Range

Item	HPLL12/6000K	HPLL12/4000K	HPLL12/3000K
Input voltage	85-265V	85-265V	85-265V
Power consumption	12W	12W	12W
Colour	6000K	4000K	3000K
Colour temperature	Daylight	Cool white	Warm white
Life time	>50,000 hrs	>50,000 hrs	>50,000 hrs
Operating temperature	-10°C to + 45°C	-10°C to + 45°C	-10°C to + 45°C
Storage temperature	-10°C to + 65°C	-10°C to + 65°C	-10°C to + 65°C
Lumen	1200lm	1140lm	1080lm
Certificates	CE, RoHS, FCC, WEEE	CE, RoHS, FCC, WEEE	CE, RoHS, FCC, WEEE
Beam angle	120°	120°	120°
LED chip current	18-19mA	18-19mA	18-19mA
CRI	80	80	80

Dimensions



Chromaticity chart



Unit O, Westmead Ind Est, Westmead Drive, Swindon, Wiltshire, SN5 7YT ${f T}$ 01793 617376 | ${f E}$ info@heathfieldled.co.uk | ${f www.heathfieldled.co.uk}$