

## 30w 1450mm linear led fern pendant range

### Features In Brief:

1. Energy saving exceeding 60%
2. Micro prism diffuser or opal
3. Instant start, no flicking, no humming
4. Connectible, surface or suspended
5. UGR<19
6. >50,000hrs (see website for details)
7. Fully dimmable and emergency options available >10,000hrs for eme (see website for details)



Heathfield LEDs linear pendant range is a perfect solution for illuminating office and open space environments. With a range of wattages and high efficiency up to 100lm/w this stylish range offers a modern and clean look to any lighting installation.

Part Number	Colour	Luminous Flux
HLIN1530/6000k	6000K	3,000 lm
HLIN1530/4000K	4000K	2,900 lm
HLIN1530/3000K	3000K	2,800 lm

## 1450mm linear led fern pendant Product Features

### 30w Range

Item	HLIN1530/6000K	HLIN1530/4000K	HLIN1530/3000K
Input voltage	AC 200-240V	AC 200-240V	AC 200-240V
Rated current	700mA	700mA	700mA
Power consumption	30W	30W	30W
Lumen output	3,000lm	2,900lm	2,800lm
Colour temperature	6000K	4000K	3000K
Life time	>50,000 hrs (>10eme)	>50,000 hrs (>10eme)	>50,000 hrs (>10eme)
Operating temperature	-10°C to + 50°C	-10°C to + 50°C	-10°C to + 50°C
Storage temperature	-10°C to + 60°C	-10°C to + 60°C	-10°C to + 60°C
Certificates	CE, RoHS	CE, RoHS	CE, RoHS
Weight	2 KGS	2 KGS	2 KGS
Dimensions	1450 x65 x 55 mm	1450 x 65 x 55 mm	1450 x 65 x 55 mm
CRI	80	80	80

### Product view

