

Heathfield 18W Cedar led 2D range

Features In Brief:

- 1. Energy saving exceeding 50%
- 2. Uniformed light distribution
- 3. Original epistar 3014 chips
- 4. Instant start, no flicking, no humming
- 5. Unique driver design
- 6. >50,000hrs (see website for details)
- 7. GR10q 4pin base

		-		-		-			
		-	-	-		•	6		
1. ····································			1.5	-	1		4.00		
		-	4	-		-			
-	-	1	-	10	15	-	10	-	
1= (G) (G) (G)	-						-	-	
œ (6							1.4	-	
e . e							10-10-10-10-10-10-10-10-10-10-10-10-10-1	œ	
							â (-	
a a		-			- 0			-	
-		c							
100 m	-	4			e				
-	-	. e						-	
								10	1

Heathfield LED 2d lamps are designed to replace the traditional fluorescent 2D lamp offering an energy saving alternative. The LED Board is constructed of high grade aluminium and the original Epistar3014 chips are powered by our own design driver to ensure stable operation and low levels of optical decay.

Part Number	Colour	Luminous Flux
H182D/LED/6000K	6000K	1850 lm
H182D/LED/4000K	4000K	1790 lm
H182D/LED/3000K	3000K	1640 lm

Unit O, Westmead Ind Est, Westmead Drive, Swindon, Wiltshire, SN5 7YT T 01793 617376 | E info@heathfieldled.co.uk | www.heathfieldled.co.uk




Heathfield 18W Cedar led 2D Features

18w Range

Item	H182D/LED/6000K	H182D/LED/4000K	H182D/LED/3000K	
Input voltage	110-244V	110-244V	110-244V	
Power consumption	18W	18W	18W	
Colour	6000K	4000K	3000K	
Colour temperature	Daylight	Cool white	Warm white	
Life time	>50,000 hrs	>50,000 hrs	>50,000 hrs	
Operating temperature	-10°C to + 65°C	-10°C to + 65°C	-10°C to + 65°C	
Storage temperature	-10°C to + 60°C	-10°C to + 60°C	-10°C to + 60°C	
Lumen	1850lm	1790lm	1640lm	
Certificates	CE, RoHS, FCC, WEEE	CE, RoHS, FCC, WEEE	CE, RoHS, FCC, WEEE	
Beam angle	120°	120°	120°	
Dimensions	190x190mm	190x190mm	190x190mm	
CRI	80	80	80	

Chromaticity diagram



18W 2D lamp image



Unit O, Westmead Ind Est, Westmead Drive, Swindon, Wiltshire, SN5 7YT T 01793 617376 | E info@heathfieldled.co.uk | www.heathfieldled.co.uk

Company Number: 7366136 Vat Reg No: GB 998 8098 25 WEEE No: WEE/HD2209U