

4ft single Willow IP65 led batten fitting

Features In Brief:

- 1. Energy saving exceeding 70%
- 2. Even light distribution
- 3. Original Epistar chips
- 4. Instant start, no flicking, no humming
- 5. Custom design light guide cover
- 6. High lumen output
- 7. >50,000hrs (see website for details)
- Emergency and dimmable options available >10,000hrs eme (see website for details)



Heathfield LED Anti Corrosive fittings are designed to replace the traditional Anti corrosive fluorescent type. This 24w version offers in excess of 2,000lm. This range also offers an emergency version, dimming and sensor options are also available on request. This product also benefits from a colour changing switch enabling switching between 3000k, 4000k and 6000k.

Part Number	Colour	Luminous Flux
HWCP124/6000k	6000K	2,550 lm
HWCP124/4000K	4000K	2,400 lm
HWCP124/3000K	3000K	1,850 lm

Unit O, Westmead Ind Est, Westmead Drive, Swindon, Wiltshire, SN5 7YT T 01793 617376 | E info@heathfieldled.co.uk | www.heathfieldled.co.uk




4ft single Willow IP65 led batten fitting Product Features


24w Range

ltem	HWCP124/6000K	HWCP124/4000K	HWCP124/3000K
Equivalent	4ft single anti corrosive	4ft single anti corrosive	4ft single anti corrosive
Total power Consumption	24W	24W	24W
Colour	Daylight	Cool White	Warm White
Colour Temperature	6000k	4000k	3000k
Life Time	>50,000 hrs (>10eme)	>50,000 hrs (>10eme)	>50,000 hrs (>10eme)
Operating Temperature	-10°C to + 45°C	-10°C to + 45°C	-10°C to + 45°C
Dimensions (mm)	1232 x 85 x 71	1232 x 85 x 71	1232 x 85 x 71
Lumen	2,550lm	2,400lm	1,850lm
Certificates	CE, RoHS,WEEE	CE, RoHS,WEEE	CE, RoHS,WEEE
Beam Angle	180°	180°	180°
Power factor	>90	>90	>90
CRI	80	80	80

Light distribution diagram



Chromaticity plot



Unit O, Westmead Ind Est, Westmead Drive, Swindon, Wiltshire, SN5 7YT T 01793 617376 | E info@heathfieldled.co.uk | www.heathfieldled.co.uk