

5ft single Willow IP65 led batten fitting

Features In Brief:

- 1. Energy saving exceeding 70%
- 2. Even light distribution
- 3. Original Epistar chips
- 4. Instant start, no flicking, no humming
- 5. Custom design light guide cover
- 6. High lumen output
- 7. >50,000hrs (see website for details)
- Emergency and dimmable options available >10,000hrs eme (see website for details)



Heathfield LED Anti Corrosive fittings are designed to replace the traditional Anti corrosive fluorescent type. This 30w version offers in excess of 2,500lm. This range also offers an emergency version, dimming and sensor options are also available on request. This product also benefits from a colour changing switch enabling switching between 3000k, 4000k and 6000k.

Part Number	Colour	Luminous Flux
HWCP130/6000k	6000K	3,150 lm
HWCP130/4000K	4000K	2,900 lm
HWCP130/3000K	3000K	2,650 lm

Unit O, Westmead Ind Est, Westmead Drive, Swindon, Wiltshire, SN5 7YT T 01793 617376 | E info@heathfieldled.co.uk | www.heathfieldled.co.uk




5ft single Willow IP65 led batten fitting Product Features


30w Range

ltem	HWCP130/6000K	HWCP130/4000K	HWCP130/3000K
Equivalent	5ft single anti corrosive	5ft single anti corrosive	5ft single anti corrosive
Total power Consumption	30W	30W	30W
Colour	Daylight	Cool White	Warm White
Colour Temperature	6000k	4000k	3000k
Life Time	>50,000 hrs (>10eme)	>50,000 hrs (>10eme)	>50,000 hrs (>10eme)
Operating Temperature	-10°C to + 45°C	-10°C to + 45°C	-10°C to + 45°C
Dimensions (mm)	1532 x 85 x 71	1532 x 85 x 71	1532 x 85 x 71
Lumen	3,150lm	2,900lm	2,650lm
Certificates	CE, RoHS,WEEE	CE, RoHS,WEEE	CE, RoHS,WEEE
Beam Angle	180°	180°	180°
Power factor	>90	>90	>90
CRI	80	80	80

Light distribution diagram



Chromaticity plot



Unit O, Westmead Ind Est, Westmead Drive, Swindon, Wiltshire, SN5 7YT T 01793 617376 | E info@heathfieldled.co.uk | www.heathfieldled.co.uk