

9W Hawthorn led downlight range

Features In Brief:

1. Energy saving exceeding 60%
2. Uniformed light distribution
3. Original Epistar chips
4. Instant start, no flicking, no humming
5. Dali/1-10v/DSI versions available
6. >50,000hrs (see website for details)
7. CE, RoHS , FCC and WEEE certificates



Heathfield LED downlights are designed to replace the traditional PL downlights commonly seen within offices and communal areas. The solid construction of this unit offers both uniformed light distribution as well as maintenance free operation. The downlight comes prewired with driver and has dimming options for 1-10v/DALI/DSI. Using original Epistar chips this unit is truly a fit and forget solution.


Part Number	Colour	Luminous Flux
HDL9/HAW/6000k	6000K	792 lm
HDL9/HAW/4000K	4000K	765 lm
HDL9/HAW/3000K	3000K	738lm

9W led Hawthorn downlight Product Features

9w Range

Item	HDL9/HAW/6000K	HDL9/HAW/4000K	HDL9/HAW/3000K
Input voltage	100-240V	100-240V	100-240V
Power consumption	9W	9W	9W
Colour temperature	Daylight	Cool white	Warm white
Life time	>50,000 hrs	>50,000 hrs	>50,000 hrs
Operating temperature	-10°C to + 65°C	-10°C to + 65°C	-10°C to + 65°C
Storage temperature	-10°C to + 60°C	-10°C to + 60°C	-10°C to + 60°C
Lumen	792lm	765lm	738lm
Beam angle	100°	100°	100°
Outer dimensions	Ø146x12mm	Ø146x12mm	Ø146x12mm
Cut out size	135mm	135mm	135mm
IP Rating	IP22	IP22	IP22
CRI	80	80	80

Chromaticity Diagram



Product dimensions

