

6ft led yew tube

Features In Brief:

- 1. Energy saving exceeding 50%
- 2. Uniformed light distribution
- 3. Original Epistar 3528 chips
- 4. Instant start, no flicking, no humming
- 5. Unique driver design
- 6. Rotatable end cap
- 7. >50,000hrs (see website for details)



Heathfield LED Tubes are designed to replace the traditional fluorescent tube offering an energy saving alternative. The tube is constructed of a high grade aluminium heat sync and custom designed light guide lens offering a uniformed light distribution. Using our specifically designed driver and original Epistar 3528 chips we can offer a stable operation with long life time claims and low optical decay levels.

Part Number	Colour	Luminous Flux
6F26LED/6000K/E	6000K	2600 lm
6F26LED/4000K/E	4000K	2550 lm
6F26LED/3000K/E	3000K	2490 lm

Unit O, Westmead Ind Est, Westmead Drive, Swindon, Wiltshire, SN5 7YT T 01793 617376 | E info@heathfieldled.co.uk | www.heathfieldled.co.uk



6ft led yew tube Product Features

26w Range

ltem	6F26LED/6000K/E	6F26LED/4000K/E	6F26LED/3000K/E
Input Voltage	85-277V	85-277V	85-277V
Power Consumption	26W	26W	26W
Colour	Daylight	Cool White	Warm White
Colour Temperature	6000k	4000k	3000k
Life Time	>50,000 hrs	>50,000 hrs	>50,000 hrs
Operating Temperature	-10°C to + 65°C	-10°C to + 65°C	-10°C to + 65°C
Storage Temperature	-10°C to + 60°C	-10°C to + 60°C	-10°C to + 60°C
Lumen	2600lm	2550lm	2490lm
Certificates	CE, RoHS, FCC, WEEE	CE, RoHS, FCC, WEEE	CE, RoHS, FCC, WEEE
Beam Angle	120°	120°	120°
LED Chip current	18-19mA	18-19mA	18-19mA
CRI	80	80	80

*Based on clear cover lens


Product View

Tube wiring specification

Mains power to be fed the label end

Emergency to be connected to non label end





To Emergency pack

Unit O, Westmead Ind Est, Westmead Drive, Swindon, Wiltshire, SN5 7YT T 01793 617376 | E info@heathfieldled.co.uk | www.heathfieldled.co.uk